

## Outside Screw and Yoke Gate Valves

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes, 3/4 through 2 in. NPS inclusive, are of bronze. Large sizes, 2 1/2 through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Model F722U

Model F722U. Resilient Seated Gate Valve. 2 1/2 through 12 in. NPS. 200 psi (1380 kPa) rated working pressure. Available with the following end connections:

2 1/2, 3, 4, 6, 8, 10, 12	Flanged
---------------------------	---------

<b>Company Name:</b>	Fluid Equipment International Ltd
<b>Company Address:</b>	Unit 14, Chancery Gate Business Center, Manor House Ave, SO15 0AE, Southampton, United Kingdom
<b>Company Website:</b>	<a href="http://www.fluid-equipment.com">http://www.fluid-equipment.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved